



TOG MOR

Vessel specifications

| | |
|----------------------------------|---|
| Length overall (incl. stinger) | 154 m (505 ft) |
| Length overall (excl. stinger) | 111 m (364 ft) |
| Breadth | 27 m (89 ft) |
| Depth to main deck | 6 m (20 ft) |
| Operating draught | 2 m (7 ft) |
| Mooring system | Flipper Delta anchors, 10 points: Forward: 4 x 10 t (20 kips) and 2 x 8.5 t (20 kips) Aft: 4 x 7 t (15 kips) |
| Total installed power | 3750 kW |
| Accommodation | 144 persons |
| Helideck | Maximum take-off weight 11.1 t, suitable for Sikorsky S-92 and Puma 100 helicopters |
| Deck cranes | Main crane of 300 t (660 kips) at 17 m (55 ft) main hoist Crawler crane of 79 t (170 kips) at 8 m (26 ft) main hoist |
| Work stations | 3 (single joint) welding stations, 1 NDT station and 1 coating stations |
| Installed tension capacity | 1 x 100 t |
| Pipe cargo capacity on main deck | 10 t/m ² |
| Pipe diameters | From 2" to 60" OD |
| Clear deck space | 1000 m ² |
| Classifications | LR A1 Barge, crane pontoon |
| Port of registry | Valletta |